

ATEX Guardian Rechargeable Portable Floodlight

Manufactured by: **NITECH**



ATEX GUARDIAN SPACELIGHT

A very powerful completely portable rechargeable floodlight providing up to 12 hours of full power illumination suitable for ATEX Zone 2 and 22 operation. The performance is fully equivalent to mains or generator task lighting and in addition to Hazardous Area operation offers other significant Health and Safety benefits including zero pollutants, silent operation, cool running and freedom from interconnecting cables and associated potential hazards.

Designed for all-weather and real-life site conditions this immensely robust floodlight is manufactured from Admiralty Grade pressure die cast powder coated aluminium with a polycarbonate/lexan lens.

The sophisticated electronic power supply and charger provide reliable operation for many thousands of hours and a major design feature allows on-site customer servicing.



Full Specification

ATEX Category 3 Certificate

Epsilon Compliance

Certificate No.	EPSILON 06 ATEX 2098X
Approvals	II 3 G D Ex nA nL IIC T4 T81C
Directive	ATEX 94/9/EC EN60079-15

Recharge Time (full)	6 to 7 hours
Operating Time (full output)	10 to 12 hours
Light Output	2000 lumens – 4000°K (cool white)
Lamp Type	2 × CFL 4 pin 11 watt
Power System	Maintenance free battery
Protection Standard	IP68 (waterproof)
Construction	Pressure die-cast aluminium Polycarbonate/lexan lens
Dimensions	As pictured: 264 × 245 × 550mm Height after folding: 290mm
Weight	8.5kg
Expected Operating Life (before service)	10,000 hours

Order code:
GU01 Guardian
Call: 0121 767 6400
Email: info@rstahl.co.uk
for further details